SAFFTY DATA SHEET

1. Identification

Product number

PART # 13-0111

Product identifier

FARM OYL BRAKE PARTS CLNR

Company information

CHS INC - STATION 705

ST. PAUL MN 55164 United States

Company phone

General Assistance

Emergency telephone US

1-866-836-8855 1-952-852-4646

Emergency telephone outside

Version #

09

Recommended use

CLEANER

Recommended restrictions

None known.

2. Hazard(s) identification

Physical hazards

Flammable aerosois

Category 1

Health hazards

Serious eye damage/eye irritation

Category 2A

Germ cell mutagenicity

Category 1B

Carcinogenicity

Category 1B

Reproductive toxicity

Category 2

Specific target organ toxicity, single exposure

Category 3 narcotic effects

Environmental hazards

Not classified.

OSHA defined hazards

Not classified.

Label elements



Signal word

Danger

Hazard statement

Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn

child.

Precautionary statement

Prevention

Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wear protective

gloves/protective clothing/eye protection/face protection.

Response

if exposed or concerned: Get medical advice/attention.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Common name and synonyms CAS number Chemical name 67-64-1 80 - 90 Acetone

Chemical name	Common name and synonyms	CAS number	%
Carbon Dioxide		124-38-9	2.5 - 10
n-Heptane		142-82-5	2.5 - 10
Solvent naphtha (petroleum), light aliph.		64742-89-8	2.5 - 10
Cyclohexane		110-82-7	0.1 - 1
Toluene		108-88-3	0.1 - 1
Other components below reportable levels		4	0.01 - 0.1

#: This substance has workplace exposure limit(s).

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Rinse mouth.

Skin contact

Get medical attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Ingestion

Most important

symptoms/effects, acute and

delayed

Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatique, dizziness and nausea.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters Fire-fighting

equipment/instructions

Specific methods

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

Extremely flammable aerosol. General fire hazards

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable, isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 2 Aerosol.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
(4=		1000 ppm	
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
•		5000 ppm	
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m3	
,		300 ppm	
n-Heptane (CAS 142-82-5)	PEL	2000 mg/m3	
		500 ppm	
US. OSHA Table Z-2 (29 CFR 1910	.1000)		
Components	Туре	Value	
Toluene (CAS 108-88-3)	Ceiting	300 ppm	
,	TWA	200 ppm	
ACGIH			
Components	Туре	Value	
Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TWA	400 ppm	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
•	TWA	5000 ppm	
Cyclohexane (CAS 110-82-7)	TWA	100 ppm	
n-Heptane (CAS 142-82-5)	STEL	500 ppm	
•	TWA	400 ppm	
Toluene (CAS 108-88-3)	TWA	20 ppm	

Product name: 14 OZ FARM OYL BRAKE PARTS CLNR LB 12PK Product #: 1000008974 Version #: 09 Issue date: 07-01-2015

119	MIOSH:	Pocket	Guide	ŧ٥	Chemical	Hazards
UO.	INIUGII.	LOWER	Guiue	w	CHCIIIICai	11040143

Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
,		250 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
,		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m3	
		300 ppm	
n-Heptane (CAS 142-82-5)	Ceiling	1800 mg/m3	
,	-	440 ppm	
	TWA	350 mg/m3	
		85 ppm	
Toluene (CAS 108-88-3)	STEL	560 mg/m3	
,		150 ppm	
	TWA	375 mg/m3	
		100 ppm	

Biological limit values

ACGIH Biological Exposu Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*	
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*	
	0.03 mg/l	Toluene	Urine	*	
	0.02 mg/l	Toluene	Blood	*	

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3)

Skin designation applies.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection

If contact is likely, safety glasses with side shields are recommended.

Hand protection

Wear appropriate chemical resistant gloves.

Skin protection

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Skin protection

Respiratory protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Clear. Liquid.

Physical state

Gas.

Form

Aerosol.

Color

clear

Odor

Solvent.

Odor threshold

Not available.

Not applicable estimated

Melting point/freezing point

Not available.

initial boiling point and boiling range

Flash point

123.68 °F (50.93 °C) estimated

-4.0 °F (-20.0 °C) Concentrate estimated

Evaporation rate

Not available.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits Flammability limit - lower

1 % estimated

6.7 % estimated

Flammability limit - upper (%)

Not available. Explosive limit - lower (%) Not available. Explosive limit - upper (%)

Vapor pressure

45 - 60 psig @ 70F estimated

Vapor density

Not available.

`Relative density

Not available.

Solubility(ies)

Solubility (water)

Not available.

Partition coefficient

Not available.

(n-octanol/water)

Auto-ignition temperature

474.8 °F (246 °C) estimated

Decomposition temperature

Not available.

Viscosity

Not available.

Other information

Specific gravity

0.77 - 0.78 estimated estimated

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use. Hazardous polymerization does not

occur.

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. Fire or intense heat may cause violent rupture of

packages.

Incompatible materials

Acids, Strong oxidizing agents, Aluminum.

Material is stable under normal conditions.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion

Expected to be a low ingestion hazard.

Inhalation

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Narcotic effects. Prolonged

inhalation may be harmful.

Skin contact

Causes mild skin irritation.

Eye contact

Causes serious eve irritation.

Symptoms related to the physical, chemical and toxicological characteristics Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting. May cause central nervous system effects.

Information on toxicological effects

Acute toxicity

Narcotic effects. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Product	Species	Test Results
	PARTS CLNR L8 12PK (CAS Mixture)	
Acute		
Dermal		
LÐ50	Rat	13340 mg/kg
Inhalation		
LC50	Rat	90 mg/l/4h
Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Demal		T. 100 A . 0.4.11
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
Oral		•
LD50	Rat	5800 mg/kg
+-		2.2 ml/kg
Cyclohexane (CAS 110-82-7	7)	•
Acute	7	
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 32880 mg/m3, 4 Hours
		> 5540 ppm, 4 Hours
n-Heptane (CAS 142-82-5)		
Acute		
Dermai		
LD50	Rabbît	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 29.29 mg/l, 4 Hours
Solvent naphtha (petroleum)	, light aliph. (CAS 64742-89-8)	
Acute	, ,	
Dermal		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 5020 mg/m3, 4 Hours
		> 4980 mg/m3
		> 4980 mg/m3, 4 Hours
		> 4.96 mg/l, 4 Hours
Oral		
(Irai		
Oral LD50	Rat	4820 mg/kg

Components	Species		Test Results			
Toluene (CAS 108-88-3)						
Acute						
Dermal						
LD50	Rabbit		> 5000 mg/kg, 24 Hours			
Inhalation						
LC50	Mouse		6405 - 7436 ppm, 6 Hours			
			5320 ppm, 8 Hours			
	Rat		5879 - 6281 ppm, 6 Hours			
			12.5 - 28.8 mg/l, 4 Hours			
Oral						
LD50	Rat		5000 mg/kg			
·		additional component data not shown.				
Skin corrosion/irritation		ild skin irritation.				
Serious eye damage/eye irritation	Causes se	rious eye irritation.				
Respiratory or skin sensitizatio	n					
Respiratory sensitization	Not a resp	iratory sensitizer.				
Skin sensitization	This produ	ct is not expected to cause skin sensitization	n.			
Germ cell mutagenicity	May cause	e genetic defects.				
Carcinogenicity	May cause	May cause cancer.				
IARC Monographs. Overall Toluene (CAS 108-88-3) OSHA Specifically Regulate)		carcinogenicity to humans.			
Not listed.						
Reproductive toxicity	May dama	ge fertility or the unborn child. Suspected of	damaging fertility or the unborn child.			
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.					
Specific target organ toxicity - repeated exposure	Not classif	ied.				
Aspiration hazard	Not an asr	piration hazard. Not likely, due to the form of	the product.			
Chronic effects	•	inhalation may be harmful.				
	_	,				
12. Ecological information	n					
Ecotoxicity	Toxic to a	quatic life with long lasting effects.				
Product		Species	Test Results			
14 OZ FARM OYL BRAKE P	ARTS CLNR	LB 12PK (CAS Mixture)				
Aquatic						
Algae	IC50	Algae	47569 mg/L, 72 Hours			
Crustacea	EC50	Daphnia	16290 mg/L, 48 Hours			
Fish	LC50	Fish	6585 mg/L, 96 Hours			
Components		Species	Test Results			
Acetone (CAS 67-64-1)						
Aquatic						
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours			
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours			
Cyclohexane (CAS 110-82-7)					
Aquatic						
·	1.000	Enthand minnous (Dimonhalos prometas	e) 23 03 - 42 07 mg/L 06 hours			

Fathead minnow (Pimephales promelas) 23.03 - 42.07 mg/l, 96 hours

Fish

LC50

Components		Species	Test Results
n-Heptane (CAS 142-82-5)			
Aquatic			
Fish	LC50	Mozambique tilapia (Tilapia mossambica)	375 mg/l, 96 hours
Solvent naphtha (petroleum)), light aliph. ((CAS 64742-89-8)	
Aquatic			
Algae	IC50	Algae	4700 mg/L, 72 Hours
Toluene (CAS 108-88-3)			
Aquatic			
Algae	IC50	Algae	433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
		Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours
* Estimates for product may	be based on	additional component data not shown.	
sistence and degradability		s available on the degradability of this product.	
accumulative potential	No data a	available.	

Per

Bio

Partition coefficient n-octanol / water (log Kow)

-0.24Acetone 3.44 Cyclohexane n-Heptane 4.66 Toluene 2.73

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1) Cyclohexane (CAS 110-82-7) Toluene (CAS 108-88-3)

U002 U056 U220

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT

UN1950 **UN** number

UN proper shipping name

Aerosols, flammable

Transport hazard class(es) Class

2.1 Subsidiary risk 2.1

Label(s) Packing group

Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82 306 Packaging exceptions Packaging non bulk None None Packaging bulk

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN1950 UN number

UN proper shipping name

Aerosols, flammable

Transport hazard class(es)

2.1 Class Subsidiary risk

Label(s) Packing 2.1

group Environmental

Not applicable.

hazards ERG Code

Yes 10L

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed.

aircraft

Cargo aircraft only

Allowed.

Packaging Exceptions

LTD QTY

IMDG

UN number

UN1950

UN proper shipping name

AEROSOLS

Transport hazard class(es)

2.1

Class Subsidiary risk

Label(s) Packing

2.1

group Environmental

Not applicable.

hazards

Marine pollutant

Yes

EmS

F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions Transport in bulk according to LTD QTY

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Cyclohexane (CAS 110-82-7) Toluene (CAS 108-88-3) Listed.

Listed. Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Cyclohexane	110-82-7	0.1 - 1
Toluene	108-88-3	0.1 - 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number Acetone (CAS 67-64-1) 6532 6594 Toluene (CAS 108-88-3) Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c)) 35 %WV Acetone (CAS 67-64-1) 35 %WV Toluene (CAS 108-88-3) DEA Exempt Chemical Mixtures Code Number 6532 Acetone (CAS 67-64-1) Toluene (CAS 108-88-3) 594 US state regulations US. Massachusetts RTK - Substance List Acetone (CAS 67-64-1) Carbon Dioxide (CAS 124-38-9) Cyclohexane (CAS 110-82-7) n-Heptane (CAS 142-82-5) Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9) Cyclohexane (CAS 110-82-7) n-Heptane (CAS 142-82-5) Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9) Cyclohexane (CAS 110-82-7) n-Heptane (CAS 142-82-5) Toluene (CAS 108-88-3)

US, Rhode Island RTK

Acetone (CAS 67-64-1) Cyclohexane (CAS 110-82-7) Toluene (CAS 108-88-3)

US, California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3)

Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3)

Listed: August 7, 2009

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Ricc	Toxic Substances Control Act (TSCA) Inventory	Yes

United States & Puerto Rico — Toxic Substances Control Act (TSCA) inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Product name: 14 OZ FARM OYL BRAKE PARTS CLNR LB 12PK

16. Other information, including date of preparation or last revision

Issue date

07-01-2015

Version #

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Product name: 14 OZ FARM OYL BRAKE PARTS CLNR LB 12PK Product #: 1000008974 Version #: 09 Issue date: 07-01-2015